

P300S+ Post driver



PROTECH



PROTECH

P300S+ Post driver

P300S+ configuration

- ✓ 300kg hammer
- ✓ 10 Feet posts capability
- ✓ Maintenance free pulley system
- ✓ External control levers
- ✓ 800mm telescopic arm
- ✓ 120-degree hydraulic slew
- ✓ 35-degree forward/back mast tilt
- ✓ 35-degree side/side mast tilt
- ✓ Hydraulic rear leg
- ✓ Quick Release 300mm throat width Gripper Plate
- ✓ Reinforced rubber on gripper for noise reduction
- ✓ Adjustable front legs
- ✓ Drawbar

Options :

- 350 kg hammer weight
- 300 kg counterweight
- 75 mm rock spike and hydraulic extractor
- Independent hydraulic front legs



120-degree slew

You can operate your machine from the ground, easily reach corners with the massive 120-degree hydraulic slew.



Hydraulic rear leg

Controlled from the control panel, brings stability in operation. Standard.



Front legs

Adjustable in height, multi-positions. Standard. Can be hydraulic as an option.

Mast tilt

Hydraulically operated from the control panel, very robust construction. Standard



Rock-spike and Extractor

75mm rock spike to go through rocky grounds, easily operated in and out. Includes the hydraulic extractor for a safe and efficient operation.

One additional lever valve. Option.



Hydraulics controls

Weather proof controls, hammer, mast shift, mast tilt both directions. One additional valve for rock spike extractor.

Good safety with robust guard.

Drawbar

Fitted as standard.



Tele-arm

800 mm telescopic arm for a long reach. Heavy duty construction with wear pads for enhanced lifetime. Standard.



PROTECH MACHINERY LTD

Woolridge Farm, Gloucester Road, Hartpury, Gloucester GL19 3BG

Tel: 01452 700713 Email: sales@protechmachinery.com

Company reg. no. 4958012 VAT no. 834 1361 48